



BATTERIES CYCLIQUES

SANS ENTRETIEN

**Vehicule
électrique
AGM**

AGM

BATTERIES

= Absorbed Glass Matt

+ HD RANGE = Maximum capacity



Réf.	Alt.	Volt (V)	C20 (Ah)	C5 (Ah)	Longueur (mm)	Largeur (mm)	Hauteur (mm)	Poids (kg)	Layout	Terminaux
6V										
DAB6-110EV		6	122,0	94,7	193	168	208	17,9	1	M8
DAB6-160EV		6	178,0	145,0	298	171	229	26,4	1	M8
DAB6-180EV*	GC2	6	210,0	167,0	260	180	252	29,5	0	M8
DAB6-200EV		6	227,0	182,0	323	178	228	31,8	1	M8
DAB6-225EV		6	243,0	198,0	244	188	275	32,8	1	M8
DAB6-260EV*	S3	6	260,0	226,0	295	180	298	36,0	0	DT 1+8
DAB6-310EV*	S4	6	310,0	246,5	295	178	350	46,0	0	M8
DAB6-330EV	S4H	6	330,0	262,5	295	178	350	46,6	0	M8
DAB6-335EV		6	315,0	255,0	295	178	350	40,6	1	M8
DAB6-380EV*	L16	6	380,0	302,0	295	178	408	55,5	0	M8
DAB6-420EV	L16H	6	420,0	334,0	295	178	408	56,8	0	M8
8V										
DAB8-160EV		8	161,0	131,0	260	182	298	36,8	1	M8
12V										
DAB12-7.5EV		12	7,7	6,3	151	65	100	2,5	3	T1
DAB12-14EV		12	12,3	10,0	151	98	106	3,9	3	T2
DAB12-18EV		12	18,5	15,5	181	76	167	5,5	0	M5
DAB12-18EV-HD		12	26,4	22,6	181	77	170	6,9	0	M5
DAB12-26EV		12	29,5	22,2	168	178	124	8,4	0	M5
DAB12-26EV-HD		12	33,6	28,0	168	178	124	8,9	0	M5
DAB12-28EV		12	29,7	24,3	166	125	175	9,1	0	M5
DAB12-33EV		12	34,0	28,0	196	131	160	10,4	1	M6
DAB12-33EV-HD		12	41,1	35,7	195	130	163	11,6	1	M6
DAB12-44EV		12	46,2	37,7	198	167	158	13,3	0	M6
DAB12-44EV-HD		12	56,0	48,0	195	165	175	15,2	0	M6
DAB12-60DEV		12	60,0	45,0	242	175	190	18,5	0	1
DAB12-55EV		12	60,7	49,8	229	138	214	17,0	1	M6
DAB12-55EV-HD		12	64,5	56,0	229	138	214	18,1	1	M6
DAB12-70DEV		12	70,0	55,0	278	175	190	21,0	0	1
DAB12-70JEV		12	73,3	58,7	349	168	176	21,6	0	M6
DAB12-80DEV		12	80,0	60,0	315	175	190	24,0	0	1
DAB12-70EV		12	86,6	71,2	260	168	212	23,6	1	M6
DAB12-80EV		12	92,0	72,8	260	168	212	24,6	1	M8
DAB12-95DEV		12	95,0	70,0	353	175	190	27,0	0	1
DAB12-100EV		12	108,0	83,9	306	168	212	30,4	1	M8
DAB12-110EV		12	118,0	94,4	329	173	210	32,5	1	M8
DAB12-120EV		12	128,0	109,0	409	177	227	37,0	1	M8
DAB12-135EV		12	166,0	136,0	342	173	286	43,3	1	M8
DAB12-150EV		12	163,0	134,0	483	170	242	44,0	1	M8
DAB12-160EV		12	181,0	146,0	530	209	217	55,0	4	M8
DAB12-200EV		12	226,0	182,0	522	242	225	63,7	4	M8
DAB12-230EV		12	254,0	208,0	521	270	208	73,5	4	M8

INFORMATIONS TECHNIQUES

Pour plus d'information concernant les fixations, les layouts, et les terminaux, se reporter en pages 98 & 99.



- BAT/33955 Automot. adaptor M6
- BAT/33956 Automot. adaptor M8



- BAT/32714 J-Type adaptor M6

* Sur demande